

# **Workflow Guide:**

# **3D Printing for Night Guards**



With SprintRay 3D printing, you can provide night guards to more patients for a fraction of the cost of other fabrication methods. This guide will walk you through the process of data gathering, design, fabrication, preparation, and placement.

# Workflow at a Glance



### 7. Prepare and Deliver

### 8. Finish and Polish



# 1. Capture Data

**Time** 

10 minutes

Tools



Intraoral scanner

### 1.1 Scan Upper, Lower, and Bite

Perform a full scan of the patient to capture their digital anatomy. Make sure there are no holes in your scan and do your best to capture as much of the surrounding tissue as possible. Complete the bite scan in a closed, resting position for best results.

Export the scans as an STL with the upper and lower arch **in occlusion**. This is the default export style for most scanners and eliminates the need for a bite scan.

# 2. Get Design

**Time** 

5 minutes



**Computer with internet** 



Patient data



SprintRay account

EMEA Workflow Guide - Night Guards Effective Date: 10.07.2023

### 2.1 Submit Treatment Request

Visit <u>dashboard.sprintray.com</u> and sign in or sign up for a SprintRay account. Select or add your patient, then choose the 'Nightguard' treatment type. Set the desired parameters and upload the patient files, then submit.

### 2.2 Review and Approve Design

SprintRay Cloud Design will provide the night guard in 1-2 business days. You'll receive an email notification when it's ready. Review and approve the file from your Cloud Design dashboard.


## 3. Create Print Job

### Time

#### 5 minutes

#### **Tools**







**SprintRay account** 

## 3.1 Import into RayWare

Once the night guard design has been approved, the 'Add To Print Job' button on the Cloud Design treatment page will automatically generate a build platform in <u>RayWare Cloud</u>.

If setting up the build platform manually, select the 'Occlusal Guard' print job type. Select the printer and resin you'll be using. We recommend printing night guards at 100 microns.

Import your design. RayWare will automatically orient the model with the intaglio facing away from the build platform and with the model at an optimal 25-degree angle with supports.

EMEA Workflow Guide - Night Guards Effective Date: 10.07.2023

### 3.2 Queue to Printer

Once you're happy with the setup of your print, select the 'Send to Queue' button, then choose the printer you'd like to use for this print job.



You can also use the 'Print Now' button, but be sure to thoroughly inspect your printer before you start printing.

# 4. 3D Print

**Time** 

60 mins




SprintRay Pro S




SprintRay NightGuard Flex resin

## 4.1 Prepare and Start the Print Job




Check that the platform is clean, locked, and ready




Check that the resin tank is seated in its cradle



Fill the tank to the max line with NightGuard Flex or Firm resin and mix to incorporate



Go to the queue and press 'Start Print'




Monitor progress on the touchscreen or on SprintRay Cloud. This print job should take around 60 minutes

# 5. Wash


**Time** 

10 mins




**ProWash** 

# 5.2 Wash the Night Guard







Transfer the build platform to ProWash


Run a standard cleaning cycle

Remove the night guard from the build platform

# 6. Post Cure

Time

8 minutes




**ProCure 2** 

### 6.2 Cure in ProCure 2




Place the night guard on the center line in ProCure 2



Select the resin you printed with, select to cure on the centerline, and press 'Start'

## **6.2 Remove Supports**




Twist the supports away from the night guard to remove. Don't worry if small support nubs are left on the guard, you'll remove them in the next step.

# 7. Smoothen and Try-in

#### Time

#### 5 minutes

#### **Tools**










Lab handpiece

**Polishing wheels** 


Dental rubber bowl of non-medicated soap and water

**Toothbrush** 

### 7.1 Smoothen and Polish




Use low RPM with a polishing wheel or carbide bur to remove any stumps left over from supports. Use 10,000-12,000 RPM.



Use a steamer and or give the night guard a rinse with warm non-medicated soap and water. Brush with a toothbrush to remove residue.

## 7.2 Patient Try-in and Adjustment



Soak the guard in a dental rubber bowl of warm water (no hotter than 50C) for 15 seconds to soften.



Seat the guard and let the patient try the appliance. Adjust chairside to achieve optimal

# 8. Finish and Polish

### **Time**

#### 5 minutes

#### **Tools**









**Muslin wheels** 



Hatho beige



Tripoli polish

**Dental lathe** 



**Pumice** 

**Steamer** (optional)



Hatho pink

(optional)

**Cotton buff** wheel (optional)




**Dental rubber bowl** with non-medicated soap and water



**Toothbrush** 


### **Pre-polish with Pumice**

Use a muslin wheel and pumice on a dental lathe with firm, consistent pressure. Reach all areas of the guard. Keep the wheel damp and the pumice flowable.



### **Polish with Tripoli**

Use a fresh muslin wheel and Tripoli. Use firm and consistent pressure, reaching all areas of the guard. Once finished, apply again and repeat using light pressure.




### **High Shine**

Use a fresh muslin wheel and Hatho beige. Use firm and consistent pressure, reaching all areas of the guard. Achieve a uniform shine across the full appliance.




### **High Gloss (Optional)**

Use a cotton buff wheel and Hatho pink. Use consistent pressure, reaching all areas of the guard until you achieve a mirror finish.



### Clean

Use a toothbrush with warm non-medicated soap and water and/or a steamer to clean the guard before delivering it to the patient.



Your night guard is now ready for delivery.